

Camden

Ceramic Colours



Wall: DECA 03 Matt

6 Colours / 2 Finishes / 2 Sizes

Camden is a modern reinterpretation of classic Majolica tiles with an undulating glazed surface and rustic imperfect edges. Available in matt or gloss, this ceramic wall-tile range provides a classic handmade look whilst effortlessly creating a contemporary feature.




Wall: DECA 08 Gloss

Sizes



DECA 01 Matt




DECA 01 Gloss



DECA 05 Gloss



DECA 06 Gloss



DECA 08 Matt




DECA 08 Gloss



DECA 04 Gloss



DECA 03 Gloss



DECA 01



	Size (mm)	Thickness	Finish	Colour Availability
1	300 x 75 (N)	9.5	Matt Gloss	DECA 01, 03 & 08 DECA 01, 04, 05, 06 & 08
2	150 x 75 (N)	9.5	Gloss	DECA 01

(N) Nominal size - pressed edge. For wall use only.
Swatch colours may vary from original. Samples should be requested.

Camden

Technical Data

Product Type: Glazed Ceramic (BS EN 14411 – Group BIII)

Use: Walls (Internal only)

Product Code: DECA

DIMENSION & SURFACE QUALITY

Technical Characteristics	Industry Standards	Requirement (for nominal size <i>N</i>)		Actual Value
		70mm ≤ <i>N</i> < 150mm	<i>N</i> ≥ 150mm	
Length & width	BS EN ISO 10545-2	± 0.75mm	± 0.50% (max. ± 2.0mm)	Conforms
Thickness	BS EN ISO 10545-2	± 0.5mm	± 10% (max. ± 0.5mm)	Conforms
Edge straightness	BS EN ISO 10545-2	± 0.5mm	± 0.30% (max. ± 1.5mm)	Conforms
Orthogonality (squareness)	BS EN ISO 10545-2	± 0.75mm	± 0.50% (max. ± 2.0mm)	Conforms
Planarity (flatness): Centre curvature	BS EN ISO 10545-2	+ 0.75mm -0.5mm	+ 0.5% (max. + 2.0mm) - 0.3% (max. - 1.5mm)	Conforms
Edge curvature	BS EN ISO 10545-2	+ 0.75mm -0.5mm	+ 0.5% (max. + 2.0mm) - 0.3% (max. - 1.5mm)	Conforms
Warpage	BS EN ISO 10545-2	± 0.75mm	± 0.5% (max. ± 2.0mm)	Conforms

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	> 10%	Conforms
Crazing resistance	BS EN ISO 10545-11	No visible defects	Resistant
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	GLA
Stain resistance	BS EN ISO 10545-14	Min. Class 3	Class 5
Reaction to fire	Based on the decision 96/603/EC and its changes	A1	A1
Recycled content			61%



All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Terms & Conditions of Sale. July 2021

DOMUS

service@domusgroup.com | t: 020 8481 9500 | domusgroup.com